



| | |
|--------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Light source | LED |
| Work equipment | Electronic ballast DALI |
| Connected load | 220 - 240 V; 50 Hz; 60 Hz |
| Power consumption | ca. 43 W |
| Standby | ca. 0,3 W |
| Power factor | env. 0,960 |
| Luminous flux | approx. 5.400 lm |
| Light type/-color | Cold white |
| Colour temperatur | approx. 4.000 K |
| Color rendering index | CRI ≥ 80 |
| Light distribution | Direct/indirect |
| Direct ratio | approx. 86 % |
| Chromaticity tolerance LED | < 3 SDCM |
| Glare control | Prism aperture |
| UGR class (4H 8H; EN 12464-1) | ≤ 22 |
| System of protection | IP 20 |
| Class of protection | I |
| Technology | Switchable |
| Operation | External |
| Housing | Sheet metal; White |
| Mains lead | Connector |
| Design | Integrated version |
| Installation dimensions | ca. 600 mm; 600 mm |
| EAN | 4013330106522 |
| Weight (net) | ca. 9 kg |
| Weight incl. packaging | ca. 10,4 kg |
| Packaging dimensions | ca. 710; 680; 90 |
| Special features | Direct and indirect light; Direct light component with edge light and light-guide technology for homogenous light exit; DALI Load 1x; System dimension 600 x 600 mm; Indirect light component with specially designed lens to brighten the ceiling |