



<b>light source</b>	LED
<b>work equipment</b>	electronic ballast DALI
<b>connected load</b>	220-240V, 50/60Hz
<b>power consumption</b>	env. 43 W
<b>standby</b>	env. 0,30 W
<b>power factor</b>	env. 0,960
<b>luminous flux</b>	approx. 5.400 lm
<b>luminous efficiency</b>	approx. 126 lm/W
<b>light distribution</b>	direct/indirect
<b>direct ratio</b>	approx. 86 %
<b>colour temperature</b>	neutral white
<b>colour temperatur</b>	approx. 4.000 K
<b>color rendering index (CRI)</b>	>= 80
<b>chromaticity tolerance LED</b>	< 3 SDCM
<b>glare control</b>	conical prismatic screen
<b>unified glare rating (4H 8H)</b>	<= 22
<b>system of protection</b>	IP 20
<b>class of protection</b>	I
<b>technology</b>	switchable; DALI; continuously dimmable
<b>operation</b>	external
<b>housing</b>	sheet metal; ws
<b>mains lead</b>	connector
<b>special features</b>	113; Direct light component with edge light and light-guide technology for homogenous light exit; DALI Load 1x; Indirect light component with specially designed lens to brighten the ceiling; grid size 575 x 575mm~