


A60 100.0%


Φ: 265 lm



60 x 60 cm Φ: 265 lm

Em: 461 lx
Emax: 712 lx
Emin: 176 lx

= 50 cm



Light source

Work equipment

Connected load

Secondary tension

Power consumption

Sec. power consumption

Standby

Power factor

Luminous flux

Luminous efficiency ¹⁾

Light type/-color

Colour temperatur

Color rendering index

Light distribution

Direct ratio

Chromaticity tolerance LED

Glare control

System of protection

Class of protection

Technology

Operation

Emergency lighting

Housing

Light source cover

Arm

Balance of articulation joints

Mains lead

Fastening

Energy efficiency class

EAN

Weight (net)

Weight incl. packaging

Packaging dimensions

Special features

LED module

Electronic plug-in transformer

100 - 240 V; AC; 50 Hz; 60 Hz

5 V

ca. 4 W

ca. 3,5 W

ca. 0,3 W

env. 0,97

approx. 265 lm

approx. 85 lm/W

Warm white

approx. 3.000 K

CRI ≥ 80

Direct

approx. 100 %

< 3 SDCM

Optics

IP 20

II with plug-in power supply, III without plug-in power supply

Continuously dimmable; DC control signal

Push button

none

Plastic; Untreated; Umbra grey

Polycarbonate (PC); Satine

Tubular aluminium section; Anodized; Tubular section upright; Titanium

Friction

ca. 1,85 m; Mains plug; CEE 7/XVI

Adaptor (accessory); Table clamp (accessory); Table base

E

4013330118709

ca. 1 kg

ca. 1,9 kg

ca. 825; 190; 130

Push button in luminaire head

¹⁾ For luminaires with separate control gear, the luminous efficacy refers to the luminaire head without control g