



CEE 7/XXVI

A60 | 100.0%       $\Phi$ : 300 lm



60 x 60 cm       $\Phi$ : 300 lm

Em: 522 lx  
Emax: 806 lx  
Emin: 199 lx



**Light source**

**Work equipment**

**Connected load**

**Secondary tension**

**Power consumption**

**Sec. power consumption**

**Standby**

**Power factor**

**Luminous flux**

**Luminous efficiency <sup>1)</sup>**

**Light type/-color**

**Colour temperatur**

**Color rendering index**

**Light distribution**

**Chromaticity tolerance LED**

**Glare control**

**System of protection/Class**

**Technology**

**Operation**

**Housing**

**Light source cover**

**Arm**

**Balance of articulation joints**

**Mains lead**

**Fastening**

**Energy efficiency class**

**EAN**

**Weight without/incl. packaging**

**Packaging dimensions**

**Special features**

LED module

Electronic plug-in transformer

100 - 240 V; AC; 50 Hz; 60 Hz

5 V

ca. 4 W

ca. 3,5 W

ca. 0,3 W

env. 0,97

approx. 300 lm

approx. 96 lm/W

Cold white

approx. 4.000 K

CRI  $\geq$  80

Direct; approx. 100 %

< 3 SDCM

Optics

IP 20; II with plug-in power supply, III without plug-in power supply

Continuously dimmable; DC control signal

Push button

Plastic; Untreated; Umbra grey

Polycarbonate (PC); Satine

Tubular aluminium section; Anodized; Tubular

section upright; Titanium

Friction

ca. 1,85 m; Mains plug; CEE 7/XXVI

Adaptor (accessory); Table clamp (accessory); Table base

E

4013330127282

ca. 1 kg; 1,9 kg

ca. 825 mm; 190 mm; 130 mm

Push button in luminaire head

<sup>1)</sup> For luminaires with separate control gear, the luminous efficacy refers to the luminaire head without control gear