



light source  
work equipment  
connected load  
power consumption  
standby  
power factor  
luminous flux  
luminous efficiency  
light distribution  
direct ratio  
colour temperature  
colour temperatur  
color rendering index (CRI)  
chromaticity tolerance LED  
glare control  
luminance (L65)  
unified glare rating (4H 8H)  
system of protection  
technology  
operation  
housing  
cover  
dimming Range  
weight (net)  
mains lead  
fastening  
configuration  
dimension  
life expectancy LED  
special features

LED  
adjustable electronic ballast, digital DALI  
220-240V, 50/60Hz  
env. 17 W  
env. 0,2 W  
env. 0,970  
approx. 2.350 lm  
approx. 138 lm/W  
direct/indirect  
approx. 40 %  
neutral white  
approx. 4.000 K  
>= 80  
< 3 SDCM  
conical prismatic screen  
<= 2700 cd/m<sup>2</sup>  
<= 16  
IP 40  
DALI; continuously dimmable  
external  
sectional aluminium; ws  
acrylic clear  
1-100%  
env. 3,3 kg  
approx. 2,0 m; with free stranded wires  
steel cable 0.3 - 0.7 m  
Single Luminaire  
L=854mm  
4  
Flicker-free; DALI Load 1x; Suitable as emergency lighting; TouchDIM - dimming via standard switch