



Light source	LED
Work equipment	Adjustable electronic ballast, digital DALI
Connected load	220 - 240 V; 50 Hz; 60 Hz
Power consumption	ca. 17 W
Standby	ca. 0,2 W
Power factor	env. 0,97
Luminous flux	approx. 2.350 lm
Light type/-color	Cold white
Colour temperatur	approx. 4.000 K
Color rendering index	CRI ≥ 80
Light distribution	Direct/indirect
Direct ratio	approx. 40 %
Chromaticity tolerance LED	< 3 SDCM
Glare control	Prism aperture
Luminance (L65)	≤ 2.700 cd/m ²
UGR class (4H 8H; EN 12464-1)	≤ 16
System of protection	IP 40
Technology	Continuously dimmable
Operation	External
Housing	Sectional aluminium; Silver
Light source cover	Acrylic (PMMA); Clear
Dimming Range	1-100%
Mains lead	With free stranded wires; End luminaire
Fastening	Steel cable 0.3 - 0.7 m
Life expectancy LED	L90B50 50.000h
Energy efficiency class	C
EAN	4013330022006
Weight (net)	ca. 3,1 kg
Weight incl. packaging	ca. 4 kg
Dimensions	848 mm
Dimensions (dimensional drawing)	L=848mm
Packaging dimensions	ca. 1.000; 190; 120
Special features	Flicker-free; DALI Load 1x; Suitable as emergency lighting; Through-wired, up to 18 m on one mains connection; Mechanical and electrical connection of the individual modules without tools; TouchDIM - dimming via standard switch