



light source  
work equipment  
connected load  
power consumption  
standby  
power factor  
luminous flux  
luminous efficiency  
light distribution  
direct ratio  
colour temperature  
colour temperatur  
color rendering index (CRI)  
chromaticity tolerance LED  
glare control  
luminance (L65)  
unified glare rating (4H 8H)  
system of protection  
technology  
operation  
housing  
cover  
dimming Range  
weight (net)  
mains lead  
fastening  
configuration  
dimension  
life expectancy LED  
special features

LED  
adjustable electronic ballast, digital DALI  
220-240V, 50/60Hz  
env. 17 W  
env. 0,2 W  
env. 0,97  
approx. 2.250 lm  
approx. 132 lm/W  
direct/indirect  
approx. 40 %  
warm white  
approx. 3.000 K  
>= 80  
< 3 SDCM  
conical prismatic screen  
<= 2700 cd/m<sup>2</sup>  
<= 16  
IP 40  
DALI; continuously dimmable  
external  
sectional aluminium; silver  
acrylic clear  
1-100%  
env. 3,1 kg  
with free stranded wires  
steel cable 0.3 - 0.7 m  
End luminaire  
L=848mm  
4  
Flicker-free; DALI Load 1x; Suitable as emergency lighting; Through-wired, up to 18 m on one mains connection; Mechanical and electrical connection of the individual modules without tools; TouchDIM - dimming via standard switch