

**Light source****Work equipment****Connected load****Power consumption****Standby****Power factor****Luminous flux****Luminous efficiency ¹⁾****Light type/-color****Colour temperatur****Color rendering index****Light distribution****Beam angle****Chromaticity tolerance LED****Glare control****Luminance (L65)****UGR class (4H 8H; EN 12464-1)****System of protection/Class****Technology****Operation****Housing****Light source cover****Dimming Range****Mains lead****Fastening****Life expectancy LED****Energy efficiency class****EAN****Weight without/incl. packaging****Dimensions (dimensional drawing)****Packaging dimensions****Special features**

LED

Adjustable electronic ballast, digital DALI

220 - 240 V; 50 Hz; 60 Hz

approx. 9,5 W

approx. 0,2 W

env. 0,970

approx. 1.000 lm

approx. 105 lm/W

Cold white

approx. 4.000 K

CRI \geq 80

Direct; approx. 100 %

86 °

< 3 SDCM

Prism aperture

 \leq 3.000 cd/m² \leq 19

IP 40

Continuously dimmable

External

Sectional aluminium; White

Acrylic (PMMA); Clear

1-100%

approx. 2 m; With free stranded wires; Single Luminaire

Steel cable 0.3 - 0.7 m

L90B50 50.000h

C

4013330030865

3,1; approx. 4,1 kg

L=854mm

approx. 1.000 mm; 190 mm; 120 mm

Flicker-free; DALI Load 1x; Suitable as emergency lighting; TouchDIM - dimming via standard switch

¹⁾ For luminaires with separate control gear, the luminous efficacy refers to the luminaire head without control gear