



light source
 work equipment
 connected load
 power consumption
 standby
 power factor
 luminous flux
 luminous efficiency
 light distribution
 direct ratio
 colour temperature
 colour temperatur
 color rendering index (CRI)
 chromaticity tolerance LED
 glare control
 luminance (L65)
 unified glare rating (4H 8H)
 system of protection
 technology
 operation
 housing
 cover
 weight (net)
 mains lead
 fastening
 dimension
 life expectancy LED
 special features

LED
 adjustable electronic ballast, digital DALI
 220-240V, 50/60Hz
 env. 26 W
 env. 0,15 W
 env. 0,980
 approx. 2.750 lm
 approx. 106 lm/W
 direct
 approx. 100 %
 neutral white
 approx. 4.000 K
 >= 80
 < 3 SDCM
 conical prismatic screen
 <= 3000 cd/m²
 <= 19
 IP 40
 DALI; continuously dimmable
 external
 sectional aluminium; ws
 acrylic clear
 env. 7,2 kg
 with free stranded wires
 steel cable 0.3 - 0.7 m
 L=2250mm
 4
 Flicker-free; DALI Load 1x; Suitable as emergency lighting; Through-wired, up to 18 m on one mains connection; Mechanical and electrical connection of the individual modules without tools; TouchDIM - dimming via standard switch