



**Light source**

**Work equipment**

**Connected load**

**Power consumption**

**Standby**

**Power factor**

**Luminous flux**

**Light type/-color**

**Colour temperatur**

**Color rendering index**

**Light distribution**

**Direct ratio**

**Chromaticity tolerance LED**

**Glare control**

**Luminance (L65)**

**UGR class (4H 8H; EN 12464-1)**

**System of protection**

**Technology**

**Operation**

**Housing**

**Light source cover**

**Mains lead**

**Fastening**

**Life expectancy LED**

**Energy efficiency class**

**EAN**

**Weight (net)**

**Weight incl. packaging**

**Dimensions**

**Dimensions (dimensional drawing)**

**Packaging dimensions**

**Special features**

LED

Adjustable electronic ballast, digital DALI

220 - 240 V; 50 Hz; 60 Hz

ca. 13 W

ca. 0,2 W

env. 0,970

approx. 1.300 lm

Warm white

approx. 3.000 K

CRI  $\geq$  80

Direct

approx. 100 %

< 3 SDCM

Prism aperture

$\leq$  3.000 cd/m<sup>2</sup>

$\leq$  19

IP 40

Continuously dimmable

External

Sectional aluminium; White

Acrylic (PMMA); Clear

ca. 2 m; With free stranded wires

Steel cable 0.3 - 0.7 m

L90B50 50.000h

C

4013330033002

ca. 3,9 kg

ca. 5,1 kg

1.128 mm

L=1128mm

ca. 1.310; 190; 120

Flicker-free; Start luminaire with mains connection;  
DALI Load 1x; Suitable as emergency lighting;  
Through-wired, up to 18 m on one mains  
connection; Mechanical and electrical connection  
of the individual modules without tools; TouchDIM  
- dimming via standard switch