



Light source	LED
Work equipment	Adjustable electronic ballast, digital DALI
Connected load	220 - 240 V; 50 Hz; 60 Hz
Power consumption	approx. 13 W
Standby	approx. 0,2 W
Power factor	env. 0,970
Luminous flux	approx. 1.350 lm
Luminous efficiency ¹⁾	approx. 103 lm/W
Light type/-color	Cold white
Colour temperatur	approx. 4.000 K
Color rendering index	CRI \geq 80
Light distribution	Direct; approx. 100 %
Beam angle	86 °
Chromaticity tolerance LED	< 3 SDCM
Glare control	Prism aperture
Luminance (L65)	\leq 3.000 cd/m ²
UGR class (4H 8H; EN 12464-1)	\leq 19
System of protection/Class	IP 40
Technology	Continuously dimmable
Operation	External
Housing	Sectional aluminium; Silver
Light source cover	Acrylic (PMMA); Clear
Dimming Range	1-100%
Mains lead	approx. 2 m; With free stranded wires; Single Luminaire
Fastening	Steel cable 0.3 - 0.7 m
Life expectancy LED	L90B50 50.000h
Energy efficiency class	C
EAN	4013330034245
Weight without/incl. packaging	3,9; approx. 5,1 kg
Dimensions (dimensional drawing)	L=1134mm
Packaging dimensions	approx. 1.310 mm; 190 mm; 120 mm
Special features	Flicker-free; DALI Load 1x; Suitable as emergency lighting; TouchDIM - dimming via standard switch

¹⁾ For luminaires with separate control gear, the luminous efficacy refers to the luminaire head without control g