



#### Light source

#### Work equipment

#### Connected load

#### Power consumption

#### Standby

#### Power factor

#### Luminous flux

#### Light type/-color

#### Colour temperatur

#### Color rendering index

#### Light distribution

#### Direct ratio

#### Chromaticity tolerance LED

#### Glare control

#### Luminance (L65)

#### UGR class (4H 8H; EN 12464-1)

#### System of protection

#### Technology

#### Operation

#### Housing

#### Light source cover

#### Mains lead

#### Fastening

#### Life expectancy LED

#### Energy efficiency class

#### EAN

#### Weight (net)

#### Weight incl. packaging

#### Dimensions

#### Dimensions (dimensional drawing)

#### Packaging dimensions

#### Special features

#### LED

Adjustable electronic ballast, digital DALI

220 - 240 V; 50 Hz; 60 Hz

ca. 10 W

ca. 0,2 W

env. 0,970

approx. 1.000 lm

Warm white

approx. 3.000 K

CRI  $\geq$  80

Direct

approx. 100 %

< 3 SDCM

Prism aperture

$\leq$  3.000 cd/m<sup>2</sup>

$\leq$  19

IP 40

Continuously dimmable

External

Sectional aluminium; Silver

Acrylic (PMMA); Clear

ca. 2 m; With free stranded wires

Steel cable 0.3 - 0.7 m

L90B50 50.000h

C

4013330036034

ca. 3,1 kg

ca. 4,1 kg

848 mm

L=848mm

ca. 1.000; 190; 120

Flicker-free; Start luminaire with mains connection;  
DALI Load 1x; Suitable as emergency lighting;  
Through-wired, up to 18 m on one mains  
connection; Mechanical and electrical connection  
of the individual modules without tools; TouchDIM  
- dimming via standard switch