



Light source	LED
Work equipment	Electronic ballast DALI
Connected load	220 - 240 V; AC; 50 Hz; 60 Hz
Power consumption	ca. 107 W; 107 W
Standby	ca. 0,5 W
Power factor	env. 0,966
Luminous flux	approx. 15.000 lm
Luminous efficiency ¹⁾	approx. 140 lm/W
Light type/-color	Cold white
Colour temperatur	approx. 4.000 K
Color rendering index	CRI ≥ 80
Light distribution	Direct/indirect
Direct ratio	approx. 13 %
Chromaticity tolerance LED	< 3 SDCM
Glare control	Prism aperture
Luminance (L65)	≤ 2.700 cd/m ²
UGR class (4H 8H; EN 12464-1)	≤ 16
System of protection	IP 20
Class of protection	I
Technology	Multiple daylight-dependent motion sensors; -
Operation	Wireless switch
Emergency lighting	none
Housing	Aluminium/plastic; Powder coatet; Silver metallic
Light source cover	Acrylic (PMMA); Structured; Satine
Arm	Steel tube; Powder-coated; Tubular section upright; Silver metallic
Luminaire base	C-form flat
Mains lead	ca. 3 m; Mains plug; CEE 7/VII
Fastening	Floor standing base
Life expectancy LED	L80B50 60.000h
Energy efficiency class	D; D
EAN	4013330062088
Weight (net)	ca. 18 kg
Weight incl. packaging	ca. 22,3 kg
Dimensions	2.024 mm
Special features	Asymmetric radiation; Flicker-free; App control; Optional LTX Cloud connection; Direct and indirect lighting component with edge light and light guide technology for a homogeneous light exit; LTX multisensor for workplace optimisation; TALK Bluetooth; Magnetic control panel, freely positionable

Free-standing luminaire YARA.single
YAS 15000/840/RX/SR/CEE/S0/C
114268000-00808383

¹⁾ For luminaires with separate control gear, the luminous efficacy refers to the luminaire head without control g

Free-standing luminaire YARA.single
YAS 15000/840/RX/SR/CEE/S0/C
114268000-00808383



CEE 7/VII

D43 ↓ 13.0% ↑ 87.0%

