Free-standing luminaire YARA.doubleU
YUS 2/15000/840/R/SR/CEE/S0/C

114268000-00813285

Waldmann
LIGHT FOR BETTER RESULTS





CEE 7/VII



Connected load	220 - 240 V; AC; 50 Hz; 60 Hz
Work equipment	Electronic ballast DALI
Power consumption	approx. 210 W; 214 W
Standby	approx. 0,5 W
Luminous flux	approx. 30.000 lm
Luminous efficiency [1]	approx. 142 lm/W
Light type/-color	Cold white
Colour temperatur	approx. 4.000 K
Color rendering index	CRI ≥ 80
Light distribution	Direct/indirect; approx. 13 %
Glare control	Prism aperture
Light source	LED
Life expectancy LED	L80B50 60.000h
Energy efficiency class	D; D
Chromaticity tolerance LED	< 3 SDCM
At-risk group	RG0/1
Luminance (L65)	≤ 2.700 cd/m²
UGR class (4H 8H; EN 12464-1)	≤ 16
System of protection/Class	IP 20; I
Technology	Presence and daylight sensor control (PIR)
Operation	Wireless switch
Housing	Aluminium/plastic; Powder coatet; Silver metallic
Light source cover	Acrylic (PMMA)
Arm	Steel tube; Powder-coated; Tubular section upright; Silver metallic
Luminaire base	C-shaped; Silver metallic
Mains lead	approx. 3 m; Mains plug; CEE 7/VII
Fastening	Floor standing base
Weight without/incl. packaging	26; approx. 30,3 kg
Packaging dimensions	0 mm; approx. 0 mm; 0 mm
Power factor	env. 0,966
EAN	4013330144791
Special features	Asymmetric radiation; Flicker-free; App control; Direct and indirect lighting component with edge light and light guide technology for a homogeneous light exit; PIR movement and daylight sensor; TALK Bluetooth; Magnetic control panel, freely positionable

[1] For luminaires with separate control gear, the luminous efficacy refers to the luminaire head without control g

Errors and technical changes excepted. Images can vary from original.
Photometric and electrical data may vary due to component tolerances.

© 12/10/2026 H.Waldmann GmbH & Co. KG