


CEE 7/VII



## Light source

## Work equipment

## Connected load

## Power consumption

## Power factor

## Luminous flux

## Luminous efficiency <sup>1)</sup>

## Light type/-color

## Colour temperatur

## Color rendering index

## Light distribution

## Direct ratio

## Chromaticity tolerance LED

## Glare control

## Luminance (L65)

## UGR class (4H 8H; EN 12464-1)

## System of protection

## Class of protection

## Technology

## Operation

## Emergency lighting

## Housing

## Light source cover

## Arm

## Luminaire base

## Mains lead

## Fastening

## Life expectancy LED

## EAN

## Weight (net)

## Weight incl. packaging

## Dimensions

## Special features

## LED

Electronic ballast DALI

220 - 240 V; AC; 50 Hz; 60 Hz

ca. 210 W; 214 W

env. 0,966

approx. 30.000 lm

approx. 142 lm/W

Cold white

approx. 4.000 K

CRI ≥ 80

Direct/indirect

approx. 13 %

< 3 SDCM

Prism aperture

≤ 2.700 cd/m<sup>2</sup>

≤ 16

IP 20

I

Presence and daylight sensor control (PIR); -

Wireless switch

none

Aluminium/plastic; Powder coatet; Silver metallic

Acrylic (PMMA)

Steel tube; Powder-coated; Tubular section

upright; Silver metallic

C-form flat

ca. 3 m; Mains plug; CEE 7/VII

Floor standing base

L80B50 60.000h

4013330144791

ca. 26 kg

ca. 30,3 kg

2.024 mm

Asymmetric radiation; Flicker-free; App control;  
Direct and indirect lighting component with edge  
light and light guide technology for a  
homogeneous light exit; PIR movement and  
daylight sensor; TALK Bluetooth; Magnetic control  
panel, freely positionable

<sup>1)</sup> For luminaires with separate control gear, the luminous efficacy refers to the luminaire head without control g