



light source  
work equipment  
connected load  
power consumption  
standby  
power factor  
luminous flux  
luminous efficiency  
light distribution  
direct ratio  
beam angle  
colour temperature  
colour temperatur  
color rendering index (CRI)  
chromaticity tolerance LED  
glare control  
luminance (L65)  
unified glare rating (4H 8H)  
system of protection  
class of protection  
technology  
operation  
housing  
weight (net)  
mains lead  
fastening  
special features

LED  
electronic ballast  
220-240V, 50/60Hz  
env. 14 W  
env. 0,20 W  
env. 0,90  
approx. 1.400 lm  
approx. 100 lm/W  
direct  
approx. 100 %  
64°  
warm white  
approx. 3.000 K  
>= 80  
< 3 SDCM  
conical prismatic screen  
<= 2100 cd/m<sup>2</sup>  
<= 19  
IP 20  
II  
DALI; continuously dimmable  
external  
sheet metal; ws  
env. 0,74 kg  
approx. 0,35 m; connector  
tension spring  
Flicker-free; integration into DALI light management systems; As supplement for room depths and walking areas; Suitable as emergency lighting; Ceiling installation without tools by means of tension springs; Low installation depth thanks to external ballast; TouchDIM - dimming via standard switch; Strain relief with the possibility of through-wiring