



| | |
|---|---|
| Light source | LED |
| Work equipment | Electronic ballast |
| Connected load | 220 - 240 V; 50 Hz; 60 Hz |
| Power consumption | ca. 63 W |
| Standby | ca. 0,25 W |
| Power factor | env. 0,980 |
| Luminous flux | approx. 6.150 lm |
| Light type/-color | Cold white |
| Colour temperatur | approx. 2.700 - 6.500 K |
| Color rendering index | CRI ≥ 90 |
| Light distribution | Direct/indirect |
| Direct ratio | approx. 40 % |
| Chromaticity tolerance LED | < 3 SDCM |
| Glare control | Prism aperture |
| Luminance (L65) | ≤ 2.700 cd/m ² |
| UGR class (4H 8H; EN 12464-1) | ≤ 16 |
| System of protection | IP 40 |
| Technology | Continuously dimmable |
| Operation | External |
| Housing | Sectional aluminium; White |
| Light source cover | Acrylic (PMMA); Clear |
| Dimming Range | 3-100% |
| Mains lead | With free stranded wires; End luminaire |
| Fastening | Steel cable 0.3 - 0.7 m |
| Life expectancy LED | L90B50 50.000h |
| Energy efficiency class | C |
| EAN | 4013330038878 |
| Weight (net) | ca. 8 kg |
| Weight incl. packaging | ca. 10,3 kg |
| Dimensions | 2.250 mm |
| Dimensions (dimensional drawing) | L=2250mm |
| Packaging dimensions | ca. 2.410; 190; 120 |
| Special features | Flicker-free; DALI Load 1x; Suitable as emergency lighting; Through-wired, up to 18 m on one mains connection; Mechanical and electrical connection of the individual modules without tools; External control required for Dali Device type 8; Constant colour temperature over the whole dimming range; Constant luminous flux between 2700 and 6500 K; Specified values at approx. 4000 K |