



**Light source**

**Work equipment**

**Connected load**

**Power consumption**

**Standby**

**Power factor**

**Luminous flux**

**Light type/-color**

**Colour temperatur**

**Color rendering index**

**Light distribution**

**Direct ratio**

**Chromaticity tolerance LED**

**Glare control**

**Luminance (L65)**

**UGR class (4H 8H; EN 12464-1)**

**System of protection**

**Technology**

**Operation**

**Housing**

**Light source cover**

**Dimming Range**

**Fastening**

**Configuration**

**Life expectancy LED**

**Energy efficiency class**

**EAN**

**Weight (net)**

**Weight incl. packaging**

**Dimensions**

**Packaging dimensions**

**Special features**

LED

Adjustable electronic ballast, digital DALI

220 - 240 V; 50 Hz; 60 Hz

ca. 23 W

ca. 0,2 W

env. 0,970

approx. 3.150 lm

Cold white

approx. 4.000 K

CRI  $\geq$  80

Direct/indirect

approx. 40 %

< 3 SDCM

Prism aperture

$\leq$  2.700 cd/m<sup>2</sup>

$\leq$  16

IP 40

Continuously dimmable

External

Sectional aluminium; White

Acrylic (PMMA); Clear

1-100%

Steel cable 0.3 - 0.7 m

Middle luminaire

L90B50 50.000h

C

4013330052188

ca. 4,5 kg

ca. 5,7 kg

600 mm

ca. 1.310; 190; 120

Flicker-free; DALI Load 1x; Suitable as emergency lighting; Through-wired, up to 18 m on one mains connection; Mechanical and electrical connection of the individual modules without tools; 90° rerouting on the right side; Continuous light without dark zone; TouchDIM - dimming via standard switch