Recessed luminaire DOTOO.line
DLE 1000/840/D

114404000-00808222

Waldmann
LIGHT FOR BETTER RESULTS





Connected load	220 - 240 V; 50 Hz; 60 Hz
Work equipment	Adjustable electronic ballast, digital DALI
Power consumption	approx. 9,5 W
Standby	approx. 0,2 W
Luminous flux	approx. 1.000 lm
Luminous efficiency [1]	approx. 105 lm/W
Light type/-color	Cold white
Colour temperatur	approx. 4.000 K
Color rendering index	CRI ≥ 80
Light distribution	Direct; approx. 100 %
Beam angle	86 °
Glare control	Prism aperture
Life expectancy LED	L90B50 50.000h
Chromaticity tolerance LED	< 3 SDCM
At-risk group	RG0/1
Luminance (L65)	≤ 3.000 cd/m²
UGR class (4H 8H; EN 12464-1)	≤ 19
System of protection/Class [2]	IP 40; 22; I
Technology	Continuously dimmable
Operation	External
Housing	Sectional aluminium; White
Light source cover	Acrylic (PMMA); Clear
Mains lead	Connector
Design	Integrated version
Fastening	Fastening bow
Weight without/incl. packaging	3,1; approx. 3,5 kg
Dimensions (dimensional drawing)	L=854mm
Packaging dimensions	990 mm; approx. 190 mm; 115 mm
Power factor	env. 0,97
EAN	4013330079116
Special features	Flicker-free; DALI Load 1x; Suitable as emergency lighting; TouchDIM - dimming via standard switch

[1] For luminaires with separate control gear, the luminous efficacy refers to the luminaire head without control g
[2] Higher degree of protection when installed.

Errors and technical changes excepted. Images can vary from original.
Photometric and electrical data may vary due to component tolerances.

www.waldmann.com
© 02/11/2026 H.Waldmann GmbH & Co. KG