


5 pin

C43 ↓46.0% ↑54.0% Φ: 10000 lm



Work equipment	Power supply unit
Connected load	220 - 240 V; AC; 50 Hz; 60 Hz
Power consumption	ca. 128 W
Luminous flux	approx. 11.090 lm
Luminous efficiency ¹⁾	approx. 86 lm/W
Light type/-color	adjustable white
Colour temperatur	approx. 3.000 - 6.500 K
Color rendering index	CRI ≥ 80
Light distribution	Direct/indirect
Chromaticity tolerance LED	< 3 SDCM
Glare control	Diffusor
System of protection/Class	IP 20; I
Technology	Switchable
Housing	Sectional aluminium; Anodised; Aluminium coloured anodised
Light source cover	Acrylic (PMMA); White opal
Mains lead	Connector; 5 pin
Design	mounted version
Fastening	Wall bracket
Maximum ambient temperature	25 °C
Life expectancy LED	L80B50 50.000h
EAN	4013330146252
Weight without/incl. packaging	ca. 6,9 kg; 8,9 kg
Packaging dimensions	ca. 133 mm; 400 mm; 1.185 mm
Special features	General light, indirect, 3000K-6500K, Ra≥80; Reading light, direct, 2700K, Ra≥90; Examination light, direct, direkt, 4000K, 60W, Ra≥95, R9≥50; DIN EN 60598-2-25; External control device required for DALI Device Type 6; Biodynamic light VTL

¹⁾ For luminaires with separate control gear, the luminous efficacy refers to the luminaire head without control gear