



| | |
|------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Light source | LED |
| Work equipment | Electronic ballast |
| Connected load | 220 - 240 V; AC; 50 Hz; 60 Hz |
| Power consumption | ca. 42 W |
| Standby | ca. 0,98 W |
| Power factor | env. 0,980 |
| Luminous flux | approx. 5.450 lm |
| Luminous efficiency ¹⁾ | approx. 129 lm/W |
| Light type/-color | dynamic white; Warm white; Daylight |
| Colour temperatur | approx. 3.000 - 6.500 K |
| Color rendering index | CRI \geq 80; R9 \geq 10 |
| Light distribution | Direct/indirect |
| Direct ratio | approx. 19 % |
| Chromaticity tolerance LED | < 3 SDCM |
| Glare control | optical film; Prism aperture |
| Luminance (L65) | \leq 1.200 cd/m ² |
| UGR class (4H 8H; EN 12464-1) | \leq 16 |
| System of protection | IP 20 |
| Class of protection | I |
| Technology | Continuously dimmable; - |
| Operation | External |
| Emergency lighting | none |
| Housing | Steel/plastic; Painted; White |
| Light source cover | Polycarbonate (PC); Clear |
| Mains lead | ca. 1 m; With free stranded wires; Single Luminaire |
| Fastening | Steel cable 0.3 - 0.7 m |
| Minimum ambient temperature | 25 °C |
| Maximum ambient temperature | 25 °C |
| Decorative contrast side parts | Flint grey |
| DALI control | DT8 Color Control DT8 |
| EAN | 4013330079536 |
| Weight (net) | ca. 8 kg |
| Weight incl. packaging | ca. 8,7 kg |
| Dimensions | 1.245 mm |
| Packaging dimensions | ca. 1.385; 300; 137 |
| Special features | Light forming; Separated, direct and indirect light individually adjustable; Integration into DALI light management system for biodynamic light VTL; DALI Load 2x; DALI - dimming via digital rotary dimmer; Specified values at approx. 4000 K |

¹⁾ For luminaires with separate control gear, the luminous efficacy refers to the luminaire head without control gear