



Light source	LED
Work equipment	Electronic ballast
Connected load	220 - 240 V; AC; 50 Hz; 60 Hz
Power consumption	approx. 57 W
Standby	approx. 0,98 W
Power factor	env. 0,980
Luminous flux	approx. 7.500 lm
Luminous efficiency ¹⁾	approx. 131 lm/W
Light type/-color	adjustable white
Colour temperatur	approx. 3.000 - 6.500 K
Color rendering index	CRI ≥ 80
Light distribution	Direct/indirect; approx. 29 %
Chromaticity tolerance LED	< 3 SDCM
Glare control	optical film; Prism aperture
Luminance (L65)	≤ 1.500 cd/m ²
UGR class (4H 8H; EN 12464-1)	≤ 16
System of protection/Class	IP 20; I
Technology	Continuously dimmable
Operation	External
Housing	Steel/plastic; Painted; White
Light source cover	Polycarbonate (PC); Clear
Mains lead	approx. 1 m; With free stranded wires; Single Luminaire
Fastening	Steel cable 0.3 - 0.7 m
Ambient temperature min./max	25 °C; 25 °C
Decorative contrast side parts	Flint grey
DALI control	DT8 Color Control DT8
Energy efficiency class	C
EAN	4013330079567
Weight without/incl. packaging	12,9; approx. 14,3 kg
Packaging dimensions	approx. 2.660 mm; 220 mm; 90 mm
Special features	Light forming; Separated, direct and indirect light individually adjustable; Integration into DALI light management system for biodynamic light VTL; DALI Load 2x; DALI - dimming via digital rotary dimmer

¹⁾ For luminaires with separate control gear, the luminous efficacy refers to the luminaire head without control g