



<b>Light source</b>	LED
<b>Work equipment</b>	Electronic ballast
<b>Connected load</b>	220 - 240 V; AC; 50 Hz; 60 Hz
<b>Power consumption</b>	approx. 57 W
<b>Standby</b>	approx. 0,98 W
<b>Power factor</b>	env. 0,980
<b>Luminous flux</b>	approx. 7.500 lm
<b>Luminous efficiency <sup>1)</sup></b>	approx. 131 lm/W
<b>Light type/-color</b>	adjustable white
<b>Colour temperatur</b>	approx. 3.000 - 6.500 K
<b>Color rendering index</b>	CRI ≥ 80
<b>Light distribution</b>	Direct/indirect; approx. 29 %
<b>Chromaticity tolerance LED</b>	< 3 SDCM
<b>Glare control</b>	optical film; Prism aperture
<b>Luminance (L65)</b>	≤ 1.500 cd/m <sup>2</sup>
<b>UGR class (4H 8H; EN 12464-1)</b>	≤ 16
<b>System of protection/Class</b>	IP 20; I
<b>Technology</b>	Continuously dimmable
<b>Operation</b>	External
<b>Housing</b>	Steel/plastic; Painted; Silver metallic
<b>Light source cover</b>	Polycarbonate (PC); Clear
<b>Mains lead</b>	approx. 1 m; With free stranded wires; Single Luminaire
<b>Fastening</b>	Steel cable 0.3 - 0.7 m
<b>Ambient temperature min./max</b>	25 °C; 25 °C
<b>Decorative contrast side parts</b>	Flint grey
<b>DALI control</b>	DT8   Color Control DT8
<b>Energy efficiency class</b>	C
<b>EAN</b>	4013330079574
<b>Weight without/incl. packaging</b>	12,9; approx. 14,3 kg
<b>Packaging dimensions</b>	approx. 2.660 mm; 220 mm; 90 mm
<b>Special features</b>	Light forming; Separated, direct and indirect light individually adjustable; Integration into DALI light management system for biodynamic light VTL; DALI Load 2x; DALI - dimming via digital rotary dimmer

<sup>1)</sup> For luminaires with separate control gear, the luminous efficacy refers to the luminaire head without control g