


CEE 7/VII

D53 ↓ 12.5% ↑ 87.5% Φ: 14050 lm
 UGR 4H 8H: <10 / <10



Light source	LED
Work equipment	Electronic ballast
Connected load	220 - 240 V; AC; 50 Hz; 60 Hz
Power consumption	ca. 93 W
Power factor	env. 0,943
Luminous flux	approx. 14.050 lm
Luminous efficiency ¹⁾	approx. 151 lm/W
Light type/-color	Cold white
Colour temperatur	approx. 4.000 K
Color rendering index	CRI ≥ 80
Light distribution	Direct/indirect; Steel tube; Painted; Tubular section upright; White approx. 12 %
Direct ratio	< 3 SDCM
Chromaticity tolerance LED	Prism aperture
Glare control	≤ 3.000 cd/m ²
Luminance (L65)	≤ 16
Unified glare rating (4H 8H) ²⁾	IP 20
System of protection	I
Class of protection	Presence and daylight sensor control (PIR); DALI
Technology	Multi-function switch
Operation	none
Emergency lighting	Steel/plastic; Painted; White
Housing	Acrylic (PMMA); Satine
Light source cover	C-form flat
Luminaire base	ca. 3 m; Mains plug; CEE 7/VII
Mains lead	Floor standing base
Fastening	Flint grey
Decorative contrast side parts	L80B50 60.000h
Life expectancy LED	4013330097127
EAN	ca. 19,7 kg
Weight (net)	2.035 mm
Dimensions	Integrated light and presence sensor PIR; Separated, direct and indirect light individually adjustable; Retrofittable with TALK module; Flicker-free; Cradle to Cradle Certified TM; Direct light component with edge light and light-guide technology for homogenous light exit; Luminaire head detachable
Special features	

¹⁾ For luminaires with separate control gear, the luminous efficacy refers to the luminaire head without control gear according to DIN EN 12464-1:2021

²⁾