



light source
 work equipment
 connected load
 power consumption
 power factor
 luminous flux
 luminous efficiency
 light distribution
 direct ratio
 colour temperature
 color rendering index (CRI)
 glare control
 luminance (L65)
 unified glare rating (4H 8H)
 system of protection
 class of protection
 technology
 operation
 housing
 cover
 arm
 luminaire base
 weight (net)
 mains lead
 fastening
 decorative contrast side parts
 special features

LED
 electronic ballast
 220-240V, 50/60Hz
 env. 206 W
 env. 0,966
 approx. 22.900 lm
 approx. 111 lm/W
 direct/indirect
 approx. 15 %
 adjustable white
 >= 80
 conical prismatic screen
 <= 3000 cd/m²
 <= 10
 IP 20
 I
 presence and daylight sensor control (PIR)
 multi-function switch; Touch-LED
 steel/plastic; painted; ws
 Acrylic satine
 steel tube; painted; tubular section upright; weiß
 C-form flat
 env. 27,6 kg
 approx. 3,0 m; mains plug; CEE 7/VII
 floor standing base
 flint grey
 integrated light and presence sensor PIR; light forming; retrofittable with TALK module; Direct light component with edge light and light-guide technology for homogenous light exit; integrated light management for biodynamic light VTL; luminaire head detachable