


CEE 7/VII

D53 | 12.3% | 87.7% Φ : 14250 lm
UGR 4H 8H: <10 / <10**Light source****Work equipment****Connected load****Power consumption****Standby****Power factor****Luminous flux****Luminous efficiency ¹⁾****Light type/-color****Colour temperatur****Color rendering index****Light distribution****Glare control****Luminance (L65)****UGR class (4H 8H; EN 12464-1)****System of protection/Class****Technology****Operation****Housing****Light source cover****Arm****Luminaire base****Mains lead****Fastening****Decorative contrast side parts****Life expectancy LED****Energy efficiency class****EPREL number of lightsources****EAN****Weight without/incl. packaging****Special features**

LED

Electronic ballast

220 - 240 V; AC; 50 Hz; 60 Hz

ca. 100 W

ca. 0,5 W

env. 0,965

approx. 14.250 lm

approx. 142 lm/W

direct static white; indirectly dynamic white

approx. 3.000 - 6.500 K

CRI \geq 80

Direct/indirect; approx. 12 %

Prism aperture

 \leq 3.000 cd/m² \leq 16

IP 20; I

Presence and daylight sensor control (PIR)

Multi-function switch

Steel/plastic; Painted; White

Acrylic (PMMA); Satine

Steel tube; Painted; Tubular section upright; White

C-form

ca. 3 m; Mains plug; CEE 7/VII

Floor standing base

Flint grey

L80B50 60.000h

C; D

1951837; 1964660

4013330003425

ca. 19,7 kg

Integrated light and presence sensor PIR;
Separated, direct and indirect light individually adjustable; Retrofittable with TALK module; Flicker-free; Cradle to Cradle Certified TM; Direct light component with edge light and light-guide technology for homogenous light exit; Indirect light component biodynamic light VTL, direct light component neutral working light; Integrated light management for biodynamic light VTL; Luminaire head detachable

¹⁾ For luminaires with separate control gear, the luminous efficacy refers to the luminaire head without control gear