



Light source	LED
Work equipment	Electronic ballast DALI
Connected load	220 - 240 V; AC; 50 Hz; 60 Hz
Power consumption	approx. 65 W
Standby	approx. 0,5 W
Power factor	env. 0,942
Luminous flux	approx. 9.350 lm
Luminous efficiency ¹⁾	approx. 143 lm/W
Light type/-color	Cold white
Colour temperatur	approx. 4.000 K
Color rendering index	CRI ≥ 80
Light distribution	Direct/indirect; approx. 19 %
Chromaticity tolerance LED	< 3 SDCM
Glare control	optical film; Prism aperture
Luminance (L65)	≤ 2.800 cd/m ²
UGR class (4H 8H; EN 12464-1)	≤ 16
System of protection/Class	IP 20; I
Technology	Continuously dimmable
Operation	External
Housing	Steel/plastic; Powder coatet; Silver metallic
Light source cover	Polycarbonate (PC); Clear
Mains lead	approx. 1 m; With free stranded wires; Single Luminaire
Fastening	Steel cable 0.3 - 0.7 m
Ambient temperature min./max	25 °C; 25 °C
Decorative contrast side parts	Flint grey
Energy efficiency class	C
EPREL number of lightsources	1288568; 1288571; 887125
EAN	4013330014599
Weight without/incl. packaging	7,5; approx. 8 kg
Packaging dimensions	approx. 1.350 mm; 290 mm; 110 mm
Special features	Flicker-free; Cradle to Cradle Certified TM; Direct light component with edge light and light-guide technology for homogenous light exit; DALI Load 2x; Integration into DALI light management systems; Canopy colour (pure white); DALI - dimming via digital rotary dimmer; TouchDIM - dimming via standard switch

¹⁾ For luminaires with separate control gear, the luminous efficacy refers to the luminaire head without control g