



| | |
|---------------------------------------|---|
| Light source | LED |
| Work equipment | Electronic ballast DALI |
| Connected load | 220 - 240 V; AC; 50 Hz; 60 Hz |
| Power consumption | ca. 112 W |
| Standby | ca. 0,5 W |
| Power factor | env. 0,939 |
| Luminous flux | approx. 16.450 lm |
| Light type/-color | Cold white |
| Colour temperatur | approx. 4.000 K |
| Color rendering index | CRI ≥ 80 |
| Light distribution | Direct/indirect |
| Direct ratio | approx. 11 % |
| Chromaticity tolerance LED | < 3 SDCM |
| Glare control | optical film; Prism aperture |
| Luminance (L65) | ≤ 2.800 cd/m ² |
| UGR class (4H 8H; EN 12464-1) | ≤ 16 |
| System of protection | IP 20 |
| Class of protection | I |
| Technology | Presence and daylight sensor control (PIR); - |
| Operation | External |
| Emergency lighting | none |
| Housing | Steel/plastic; Powder coatet; White |
| Light source cover | Polycarbonate (PC); Clear |
| Mains lead | ca. 1 m; With free stranded wires; Single Luminaire |
| Fastening | Steel cable 0.3 - 0.7 m |
| Minimum ambient temperature | 25 °C |
| Maximum ambient temperature | 25 °C |
| Decorative contrast side parts | Flint grey |
| Energy efficiency class | C |
| EAN | 4013330016036 |
| Weight (net) | ca. 7,5 kg |
| Weight incl. packaging | ca. 8 kg |
| Dimensions | 1.245 mm |
| Packaging dimensions | ca. 1.350; 290; 110 |
| Special features | Integrated light and presence sensor PIR; Separated, direct and indirect light individually adjustable; Retrofittable with TALK module; Flicker-free; Cradle to Cradle Certified TM; Direct light component with edge light and light-guide technology for homogenous light exit; Push button in luminaire head; Canopy colour (pure white) |