



Light source	LED
Work equipment	Electronic ballast DALI
Connected load	220 - 240 V; AC; 50 Hz; 60 Hz
Power consumption	ca. 158 W
Standby	ca. 0,5 W
Power factor	env. 0,958
Luminous flux	approx. 24.000 lm
Light type/-color	Cold white
Colour temperatur	approx. 4.000 K
Color rendering index	CRI ≥ 80
Light distribution	Direct/indirect
Direct ratio	approx. 14 %
Chromaticity tolerance LED	< 3 SDCM
Glare control	optical film; Prism aperture
Luminance (L65)	≤ 2.700 cd/m ²
UGR class (4H 8H; EN 12464-1)	≤ 16
System of protection	IP 20
Class of protection	I
Technology	Presence and daylight sensor control (PIR); -
Operation	External
Emergency lighting	none
Housing	Steel/plastic; Powder coatet; White
Light source cover	Polycarbonate (PC); Clear
Mains lead	ca. 1 m; With free stranded wires; Single Luminaire
Fastening	Steel cable 0.3 - 0.7 m
Minimum ambient temperature	25 °C
Maximum ambient temperature	25 °C
Decorative contrast side parts	Flint grey
Energy efficiency class	C
EAN	4013330020095
Weight (net)	ca. 14 kg
Weight incl. packaging	ca. 16 kg
Dimensions	2.430 mm
Packaging dimensions	ca. 2.675; 235; 110
Special features	Integrated light and presence sensor PIR; Separated, direct and indirect light individually adjustable; Retrofittable with TALK module; Cradle to Cradle Certified TM; Direct light component with edge light and light-guide technology for homogenous light exit; Push button in luminaire head; Canopy colour (pure white)