



Light source	LED
Work equipment	Electronic ballast
Connected load	220 - 240 V; AC; 50 Hz; 60 Hz
Power consumption	ca. 210 W
Standby	ca. 0,5 W
Power factor	env. 0,966
Luminous flux	approx. 30.500 lm
Luminous efficiency <sup>1)</sup>	approx. 145 lm/W
Light type/-color	Cold white
Colour temperatur	approx. 4.000 K
Color rendering index	CRI ≥ 80
Light distribution	Direct/indirect
Direct ratio	approx. 12 %
Chromaticity tolerance LED	< 3 SDCM
Glare control	Prism aperture
Luminance (L65)	≤ 3.000 cd/m²
UGR class (4H 8H; EN 12464-1)	≤ 16
System of protection	IP 20
Class of protection	I
Technology	Presence and daylight sensor control (PIR); -
Operation	Multi-function switch; Touch-LED
Emergency lighting	none
Housing	Steel/plastic; Painted; Silver metallic
Light source cover	Acrylic (PMMA); Satine
Arm	Steel tube; Painted; Tubular section upright; Silver metallic
Luminaire base	C-form flat
Mains lead	ca. 3 m; Mains plug; CEE 7/VII
Fastening	Floor standing base
Decorative contrast side parts	Flint grey
Life expectancy LED	L80B50 60.000h
Energy efficiency class	C; D
EAN	4013330118761
Weight (net)	ca. 27,6 kg
Dimensions	2.035 mm
Special features	Integrated light and presence sensor PIR; Asymmetric radiation; Separated, direct and indirect light individually adjustable; Retrofittable with TALK module; Flicker-free; Direct light component with edge light and light-guide technology for homogenous light exit; Luminaire head detachable

**Free-standing luminaire LAVIGO**  
**DPS 30000/840/R/G2A**  
121841000-00808535

---

<sup>1)</sup> For luminaires with separate control gear, the luminous efficacy refers to the luminaire head without control g

Free-standing luminaire LAVIGO  
DPS 30000/840/R/G2A  
121841000-00808535



CE



CEE 7/VII

D53 | 11.5% ↑ 88.5%      Φ: 15250 lm  
UGR 4H 8H: <10 / <10

