

# Suspended luminaire

VIVAA 2.0 C 600 D16144000-00810063

# Waldmann **W**

ENGINEER OF LIGHT.



**Derungs**   
LIGHT FOR PEOPLE

<b>fitted with</b>	6 x LED module - Energy efficiency category A+
<b>light distribution</b>	direct/indirect
<b>color rendering index (CRI)</b>	> 90, R9 > 50
<b>colour temperatur</b>	4000 K
<b>work equipment</b>	electronic converter
<b>connected load</b>	220-240 V; 50-60 Hz
<b>mains lead</b>	2 m direct power supply
<b>luminaire body</b>	aluminium
<b>weight (net)</b>	7.5 kg
<b>Power consumption</b>	85 W
<b>luminous flux</b>	10200 lm
<b>luminous efficacy</b>	120 lm/W
<b>lamp cover</b>	Acrylic satine single switchable, continuously dimmable
<b>class of protection</b>	I
<b>Accessory</b>	Casambi module, Lampshade
<b>norms</b>	EN 60598-1
<b>Room height</b>	270 - 420 cm, ceiling clearance 50 - 200 cm
<b>special features</b>	Suitable for screen work according to EN 12464-1, DALI Load 2x
<b>Fastening</b>	Ceiling mount (textile cable pendant red)
<b>Glare-free</b>	Microprisms
<b>System of protection</b>	IP 20
<b>order number</b>	D16144000 - white

## light distribution

